
## **Photopolymer Plate Processing Equipment**

## 3ES-COMBI-FPK50

## Exposure/Washout/Dryer



#### 3ES-COMBI-FPK50

All-in one system, Exposure, Washout and Dryer up to a format size of 500 x 700 mm.

- LCD Control Panel, easily customize and setup for 9 different programs

#### Washout

- Equipped with flat brush, rotating plate board and temperature control between 15°C to 65°C ( ±2°C )
- Excellent permanent self-adhesive sticky plate board for foil based plates and Magnetic plate board for metal based plates
- Plate thickness adjustment

#### Exposure

- UVA exposing lamps
- Powerful and fast vacuum system and vacuum indicator on control panel
- Defective lamp indicator
- Lamp temperature control and regulation
- End of job alert

### Drying

- Two drying drawer
- Timer for each drawer
- Uniform temperature distribution for excellent drying and plate dimensional stability
- Programmable drying temperature between 15°C to 65°C (±2°C)










# **Photopolymer Plate Processing Equipment**

## 3ES-COMBI-FPK50

# Exposure/Washout/Dryer



# Technical Data

Product Name	3ES-COMBI-FPK50
Maximum Plate Size	500 x 700 mm
Plate Type	Letterpress plate / Water-wash
Washout Tank Capacity	64 liters
<b>Environmental Requirements</b>	Temperature: 15°C to 30°C Humidity: 40% -60%
Fresh Water Connection	R3/4"
Washing Solution Outlet	Ø20 mm
Overflow Outlet	Ø20 mm
Compressed Air	6 bar minimum - 2001/min (For automatic lid opening-closing option)
Nominal Power	6.0kW
Nominal Current	10A 400 V AC (3 Ph/N/PE)50/60 Hz
Weight	275 kg net / 310 kg gross
Dimension ( WxLxH)	1120*1020*1180 mm
Crate Dimension (approx.)	1220*1120*1430 mm



For all other information's or request please contact Mega.....







