
Photopolymer Plate Processing Equipment

3ES-COMBI-FPK50s

Exposure/Washout/Dryer



3ES-COMBI-FPK50s

All-in one system, Exposure, Washout and Dryer up to a format size of 500 x 700 mm.

- Stainless steel body, 7" Touch screen panel, easily customize and setup for 9 different programs
- End of job alert

Washout

- Equipped with flat brush, rotating plate board and temperature control between 15°C to 50°C (±2°C)
- Excellent permanent self-adhesive sticky plate board for foil based plates and Magnetic plate board for metal based plates
- Automatic plate thickness adjustment
- Automatic lid opening/closing

Exposure

- UVA exposing lamps
- Powerful and fast vacuum system and vacuum indicator on control panel
- Defective lamp indicator
- Lamp temperature control and regulation

Post Expsoure

- UVA exposing lamps

Drying

- Two drying drawer
- Timer for each drawer
- Uniform temperature distribution for excellent drying and plate dimensional stability
- Programmable drying temperature between 15°C to 65°C (±2°C)










Photopolymer Plate Processing Equipment

3ES-COMBI-FPK50s

Exposure/Washout/Dryer



Technical Data

Product Name	3ES-COMBI-FPK50s
Maximum Plate Size	500 x 700 mm
Plate Type	Letterpress plate / Water-wash
Washout Tank Capacity	64 liters
Environmental Requirements	Temperature: 15°C to 30°C Humidity: 40% -60%
Fresh Water Connection	R3/4"
Washing Solution Outlet	Ø20 mm
Overflow Outlet	Ø20 mm
Compressed Air	6 bar minimum
Nominal Power	6.0kW
Nominal Current	10A 400 V AC (3 Ph/N/PE)50/60 Hz
Weight	275 kg net / 310 kg gross
Dimension (WxLxH)	1120*1020*1180 mm
Crate Dimension (approx.)	1220*1120*1430 mm



For all other information's or request please contact Mega.....







